(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date 9 October 2003 (09.10.2003)

PCT.

(10) International Publication Number WO 03/083280 A1

(51) International Patent Classification7:

F02M 43/02

(21) International Application Number: PCT/US02/06659

(22) International Filing Date: 26 March 2002 (26.03.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant and

(72) Inventor: MOODY, John, A. [US/US]; 4424 Brandywine Street, N.W., Washington, DC 20016 (US).

(74) Agents: TURNER, Richard, C. et al.; SUGHRUE MION, PLLC, 2100 Pennsylvania Avenue, N.W., Suite 800, Washington, DC 20037-3213 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: VARIABLE OCTANE DUEL FUEL DELIVERY SYSTEM



(57) Abstract: Variable octane gasoline fuel system which includes two different octane gasoline fuels, each stored in its own separate vehicle-mounted tank or compartment. These separately-stored high and low octane fuels a mixed, for example, in the vehicle's fuel injection system in proportion as necessary to meet the anti-knock requirement according to instantaneous engine load. The percentage of each octane can be controlled by the pressure in the intake manifold and other factors.

r